

6-2000

On the Optimal Choice of Quality Metric in Image Compression

Olga Kosheleva

The University of Texas at El Paso, olgak@utep.edu

Vladik Kreinovich

The University of Texas at El Paso, vladik@utep.edu

Yeung Yam

Follow this and additional works at: https://scholarworks.utep.edu/cs_techrep



Part of the [Computer Engineering Commons](#)

Comments:

UTEP-CS-00-25a.

Published in the Proceedings of the International Symposium on Smart Structures and Microsystems (IS3M), Hong Kong, October 19-21, 2000, Paper C3-3.

Recommended Citation

Kosheleva, Olga; Kreinovich, Vladik; and Yam, Yeung, "On the Optimal Choice of Quality Metric in Image Compression" (2000). *Departmental Technical Reports (CS)*. 484.

https://scholarworks.utep.edu/cs_techrep/484

This Article is brought to you for free and open access by the Computer Science at ScholarWorks@UTEP. It has been accepted for inclusion in Departmental Technical Reports (CS) by an authorized administrator of ScholarWorks@UTEP. For more information, please contact lweber@utep.edu.

On the Optimal Choice of Quality Metric in Image Compression

Olga Kosheleva

Vladik Kreinovich

Yeung Yam

Dept. of Electrical and
Computer Engineering
University of Texas
El Paso, TX 79968, USA

Dept. Computer Science
University of Texas
El Paso, TX 79968, USA
vladik@cs.utep.edu

Dept. of Mechanical &
Automation Engineering
The Chinese University of
Hong Kong

Abstract

There exist many different lossy compression methods, and most of these methods have several tunable parameters. In different situations, different methods lead to different quality reconstruction, so it is important to select, in each situation, the best compression method. A natural idea is to select the compression method for which the average value of some metric $d(I, \tilde{I})$ is the smallest possible. The question is then: which quality metric should we choose? In this paper, we show that under certain reasonable symmetry conditions, L^p metrics $d(I, \tilde{I}) = \int |I(x) - \tilde{I}(x)|^p dx$ are the best, and that the optimal value of p can be selected depending on the expected relative size r of the informative part of the image.

1 Formulation of the Problem

1.1 Image Compression Is Necessary

Images tend to take up a lot of computer space, so in many applications, where we cannot store the original images, we must use image compression. Ideally, we would like to use a lossless compression, but unfortunately, there are serious limitations on how much we can compress without losing information. For a more radical compression, we must therefore use lossy compression schemes. In these schemes, some information about the image is lost; as a result, for every point x , the intensity $\tilde{I}(x)$ of reconstructed image \tilde{I} at this point may be slightly different from the intensity $I(x)$ of the original image I at this point.

1.2 It Is Important to Select Optimal (Or At Least Good Enough) Compression Scheme

There exist many different compression schemes, from standard ones like gif, jpg, jpg2000, etc., to specially designed ones. Most of these schemes comes with one or several parameters which we can select.

One of the reasons why so many different schemes co-exist is that in different applications, different schemes (with different values of parameters) work better. It is vitally important to select an appropriate compression scheme, i.e., a scheme which provides the best compression ratio within the same accuracy. How can we do that?

1.3 The Notion of a Quality Metric

Intuitively, the quality of a compression scheme can be characterized by how close the decompressed image is to the original one. In other words, the quality of a compression scheme can be described by using an appropriate *metric* $d(I, \tilde{I})$ on the set of all images. Such metrics describing the “distance” $d(I, \tilde{I})$ between the two images I and \tilde{I} are called *quality metrics*.

1.4 It Is Important to Select Optimal (Or At Least Good Enough) Quality Metric

If we select a quality metric, then we can choose the optimal compression scheme as the one for which the average value of the selected metric is the smallest possible. So, within this approach, in order to select the optimal compression scheme, we must first select the appropriate quality metric.

In some cases, it is clear how to select the quality metric. For example, in some practical applications, we are interested in only one characteristic $c(I)$ of the

observed image I : e.g., we may only need to know the total intensity $c(I)$ within a certain zone which characterizes the tumor size. In such cases, our goal is to reconstruct the value $c(I)$ as closely as possible, so we can take the absolute value $|c(I) - c(\tilde{I})|$ of the difference $c(I) - c(\tilde{I})$ as the desired metric $d(I, \tilde{I}) = |c(I) - c(\tilde{I})|$. In such applications, the choice of the best compression is straightforward: there is no need to store the entire image I , it is sufficient to store only the single value $c(I)$ as the compressed image. This compression is, in general, extremely lossy, but from the viewpoint of the problem of reconstructing the value $c(I)$, this compression is lossless.

Similarly, if we intend to use only a few characteristics $c_i(I)$ ($1 \leq i \leq m$) of an image I , it is natural to compress an image I by storing only the values of these characteristics $c_1(I), \dots, c_m(I)$. Thus, we get a drastic compression ratio and a perfect reconstruction of all desired values $c_i(I)$.

In many practical situations, however, we do not know *a priori* which characteristics we will be interested in; depending on the situation, we may use the stored image to evaluate many different characteristics. How can we determine the metric in this case?

The larger the difference $\Delta I(x) = \tilde{I}(x) - I(x)$ between the two images, the larger the "distance" $d(I, \tilde{I})$ should be. Thus, it is natural to define the desired distance in terms of the difference $\Delta I(x)$. The question is: how exactly?

1.5 What We Are Planning to Do

In this paper, we propose a three-step solution to this question:

- First, we use some reasonable arguments to describe a general class of quality metrics.
- Second, we use natural symmetry requirements to select a subclass of quality metric characterized by a single parameter p .
- Finally, we show how to select the best value of the parameter p depending on the image.

As a result, we get a data-driven technique for selecting the optimal quality metric and thus, of the optimal compression scheme.

2 First Step: Using Reasonable Arguments to Select a General Class Of Quality Metrics

2.1 How to Describe Preferences? There Exists a General Formalism

The necessity to describe *preferences*, i.e., to describe the *utility* of different alternatives for different people, is extremely important in decision making, including decision making under conflict (also known under a somewhat misleading name of *game theory*). To describe these preferences (utilities), a special *utility theory* has been developed; see, e.g., [2, 9, 10, 12].

The mathematical formalism of utility theory comes from the observation that sometimes, when a person faces several alternatives A_1, \dots, A_n , instead of choosing one of these alternatives, this person may choose a *probabilistic* combination of them, i.e., A_1 with probability p_1 , A_2 with a probability p_2 , etc. For example, if two alternatives are of equal value to a person, that person will probably choose the first one with probability 0.5 and the second one with the same probability 0.5. Such probabilistic combinations are called (somewhat misleadingly) *lotteries*. In view of this realistic possibility, it is desirable to consider the preference relation not only for the original alternatives, but also for arbitrary lotteries combining these alternatives. Each original alternative A_i can be viewed as a *degenerate* lottery, in which this alternative A_i appears with probability 1, and every other alternative $A_j \neq A_i$ appear with probability 0.

The main theorem of utility theory states that if we have an ordering relation $L \succ L'$ between such lotteries (with the meaning " L is preferable to L' "), and if this relation satisfies natural consistency conditions such as transitivity, etc., then there exists a function u from the set \mathcal{L} of all possible lotteries into the set R of real numbers for which:

- $L \succ L'$ if and only if $u(L) > u(L')$, and
- for every lottery L , in which each alternative A_i appears with probability p_i , we have

$$u(L) = p_1 \cdot u(A_1) + \dots + p_n \cdot u(A_n).$$

This function u is called a *utility function*. Each consistent preference relation can thus be described by its utility function.

The correspondence between preference relations and utility functions is not 1-1: different utility functions may correspond to the same preference. For example, if the preference relation is consistent with the

utility function $u(L)$, then, as one can easily see, it is also consistent with the function $u'(L) = a \cdot u(L) + b$, in which a is an arbitrary positive real number, and b is an arbitrary real number.

It is known that such linear transformations form the only non-uniqueness of utility function: namely, if two utility functions $u(L)$ and $u'(L)$ describe the same preference relation, then $u'(L) = a \cdot u(L) + b$ for some real numbers $a > 0$ and b .

2.2 Application to our problem

In general, preference relations can be described by utility functions. Therefore, to describe preferences between images, we need a utility function that is defined on the set of all possible images.

In particular, if we consider realistic images I that consist of finitely many pixels and are thus described by a matrix with components I_{ij} , $1 \leq i, j \leq N$, then we need a utility function that depends on N^2 parameters ΔI_{ij} :

$$u(\Delta I) = u(\Delta I_{11}, \dots, \Delta I_{1N}, \dots, \Delta I_{N1}, \dots, \Delta I_{NN}).$$

What function should we choose? An important feature of many image processing problems, including the two above problems, is their *localness*: different parts of the image are pretty much independent on each other. Let us explain what we mean on the above examples:

- In *astronomy*, the relative quality of two possible reconstructions of a part of this image (a part that contains, e.g., a galaxy), does not depend on the remaining part of the image.
- In *medicine*, the relative quality of reconstructing a part of the mammogram does not depend on whether there is anything in the rest of this mammogram.

In mathematical terms, if

- an image I_{ij} is preferable to an image I'_{ij} that differs from I_{ij} only in pixels (i, j) from some set P , and
- images \tilde{I}_{ij} and \tilde{I}'_{ij} coincide with each other for $(i, j) \notin P$ and with, correspondingly, I_{ij} and I'_{ij} for $(i, j) \in P$,

then $\tilde{I} \succ \tilde{I}'$.

This “localness” (“independence”) is a frequent feature in practical problems, and utility theory has developed a precise description of utility functions that

satisfy this property. Namely, it has been shown that when alternatives are characterized by n parameters p_1, \dots, p_n , then the localness of the preference is equivalent to the utility function $u(p_1, \dots, p_n)$ being of one of the two types [3]:

- *additive* $u(p_1, \dots, p_n) = u_1(p_1) + \dots + u_n(p_n)$ for some functions $u_i(p_i)$; or
- *multiplicative* $u(p_1, \dots, p_n) = u_1(p_1) \cdot \dots \cdot u_n(p_n)$ for some functions $u_i(p_i)$.

In utility theory, the values $u_i(p_i)$ are called *marginal utilities*.

For images, $n = N^2$, parameters p_1, \dots, p_n are the values of the difference $\Delta I_{ij} = \Delta I(x_{ij})$ at different points x_{ij} of the grid, and the resulting forms of the utility function are

$$u(\Delta I) = \sum_{ij} u_{ij}(\Delta I_{ij})$$

and

$$u(\Delta I) = \prod_{ij} u_{ij}(\Delta I_{ij}).$$

So, to describe the utility function, we must describe how the value of the marginal utility depends on the point x_{ij} and on the brightness $\Delta I_{ij} = \Delta I(x_{ij})$ at this point. We can describe this dependence explicitly if, instead of the abbreviated notation ΔI_{ij} , we use $\Delta I(x_{ij})$, and if we describe the dependency $u_{ij}(\Delta I_{ij})$ as $U(x_{ij}, \Delta I(x_{ij}))$. In this case, the formula for the utility function takes one of the forms $u(\Delta I) = \sum U(x_{ij}, \Delta I(x_{ij}))$ or $u(\Delta I) = \prod U(x_{ij}, \Delta I(x_{ij}))$.

So far, we were analyzing the problem of how to compare different pixel-by-pixel images. In real-life, the object whose image we want to describe is continuous, pixels are simply a useful approximation. It is, therefore, desirable to reconstruct not just the values on a grid, but also the entire brightness distribution, i.e., the values of $\Delta I(x)$ for every point x . To achieve this goal, we must be able to compare the quality of different functions $\Delta I(x)$, i.e., we must be able to describe the value of utility $u(\Delta I)$ for different functions ΔI .

The denser the pixels (i.e., the smaller the distances h_x and h_y between the neighboring pixels), the closer the pixel-by-pixel image to the continuous one. Therefore, as a utility $u(\Delta I)$ of a function ΔI , we can take the *limit* of the utilities of its pixel-by-pixel representation as $h_x \rightarrow 0$ and $h_y \rightarrow 0$. How can we describe such a limit?

This limit is easy to describe for the case when utility is a *sum* of marginal utilities: in this case, the sums

are, in effect, integral sums, and therefore, as the pixels get denser, the sums tend to the integral

$$u(\Delta I) = \int U(x, \Delta I(x)) dx.$$

For the case when utility is a *product* of marginal utilities, the limit can be obtained indirectly: indeed, since utility is a product of marginal utilities, its *logarithm* is the *sum* of logarithms of marginal utilities:

$$v(\Delta I) = \log(u(\Delta I)) = \sum V(x_{ij}, \Delta I(x_{ij})),$$

where $V = \log(U)$. For these logarithms, we also get integral sums and therefore, a reasonable limit expression:

$$v(\Delta I) = \int V(x, \Delta I(x)) dx,$$

and $u(\Delta I) = \exp(v(\Delta I))$. Our goal is to find a compression method for which $u(\Delta I) \rightarrow \min$. Since logarithm is monotonic, the condition $u(\Delta I) \rightarrow \min$ is equivalent to $v(\Delta I) = \log(u(\Delta I)) \rightarrow \min$. Therefore, in multiplicative case, we get the same problem $\int V(x, \Delta I(x)) dx \rightarrow \min$ as in the additive case.

2.3 Shift-invariance

The “quality” of a compression scheme should not change if we simply shift the image. Thus, the function U should not explicitly depend on x , i.e., and we should have $d(I, \tilde{I}) = \int U(\Delta I(x)) dx$.

Since we interpret a metric as a distance, we want the metric to be equal to 0 when the compression is lossless, i.e., when $\Delta I(x) = 0$ for all x . Thus, we want $U(0) = 0$. It is also reasonable to require that the function $U(z)$ be everywhere differentiable (i.e., smooth).

3 Second Step: Using Natural Symmetry Requirements to Select a 1-Parametric Subclass of Quality Metrics

Once a metric $d(I, \tilde{I})$ is fixed, we can determine which compression is better: if $d(I, \tilde{I}_1) < d(I, \tilde{I}_2)$, then the compression which leads to \tilde{I}_1 is clearly better.

In principle, we can use different units to measure the image’s intensity. When we select a new unit which is λ times smaller than the old one, then the numerical values of intensity $I(x)$, $\tilde{I}(x)$, and $\Delta I(x)$ gets multiplied by λ : $\Delta I_{\text{new}}(x) = \lambda \cdot \Delta I_{\text{old}}(x)$. As a result, the numerical value of the metric may change.

It is, however, reasonable to expect the mere change of the measuring unit should not affect our conclusion on which compression was better. Thus, we arrive at the following definition:

Definition. By a *quality metric*, we mean the expression of the type $B(\Delta I) = \int U(\Delta I(x)) dx$ for some differentiable function $U(z)$ for which $U(0) = 0$. We say that a quality metric is *unit-invariant* if for every $\lambda > 0$, the inequality $B(\Delta I_1) < B(\Delta I_2)$ implies that $B(\lambda \cdot \Delta I_1) < B(\lambda \cdot \Delta I_2)$.

Theorem. The only unit-invariant quality metrics are the L^p -metrics $B(\Delta I) = \text{const} \cdot \int |\Delta I(x)|^p dx$ for $p \geq 1$.

For readers’ convenience, the proof is given in the Appendix.

Comment. The L^p -quality metrics are indeed widely used. The value $p = 2$ (corresponding to the mean square decompression error) is most widely used, because for $p = 2$, the optimality criterion is quadratic, and thus, when we minimize it by equating the derivatives to 0, we get an easy-to-solve linear system of equations. However, in many cases, different values of p lead to better compressions.

So, the question is: how to select the value p which is the best for a given practical problem?

4 Final Step: Selecting the Parameter p of the Quality Metric

4.1 Our Main Idea

We are interested in the values of several characteristics $c(I)$ of the image I . Instead of using the original image I , we use a degraded image $\tilde{I} = I - \Delta I$. Since the corruption is small, we can neglect the terms quadratic in ΔI in the expression for the resulting error $\Delta c = c(\tilde{I}) - c(I)$, and get a linear integral expression $\Delta c = \int \Delta I(x) \cdot a(x) dx$ for some function $a(x)$.

For each choice of the parameter p , the only information that we have about the difference ΔI is the upper bound D on the corresponding distance $d(I, \tilde{I}) = \int |\Delta I(x)|^p dx$. According to the Hölder-Minkowski inequality (see, e.g., [1], Section 4.11.2), for every two integrable functions $f(x)$ and $g(x)$, and for every two real numbers $p, q \geq 1$ for which $1/p + 1/q = 1$, we have

$$\left| \int f(x) \cdot g(x) dx \right| \leq \left(\int |f(x)|^{1/p} dx \right)^{1/p} \cdot \left(\int |g(x)|^{1/q} dx \right)^{1/q}.$$

Moreover, it is known that for any function $g(x)$, the largest possible value of $|\int f(x) \cdot g(x) dx|$ over all functions $f(x)$ with a given L^p -norm $\|f\|_p = (\int |f(x)|^{1/p} dx)^{1/p}$ is equal to $\|f\|_p \cdot \|g\|_q$, where $\|g\|_q = (\int |g(x)|^{1/q} dx)^{1/q}$. Thus, we can conclude that the best possible upper bound for $|\Delta c|$ is the product $D^{1/p} \cdot A^{1/q}$, where $1/p + 1/q = 1$ and $A = \int |a(x)|^q dx$. It is therefore reasonable to choose p for which the maximum of this product (over the functions $a(x)$ which correspond to all desired characteristics $c(I)$) is the smallest possible.

4.2 Case Study: Description

As a case study, we take the imaging problems in which the goal is to find the center of gravity of the bright zone, e.g., the center of a tank or the center of a tumor in a medical image. Let us show how, in these problems, we can estimate the values D and A and how we can find the optimal value of p .

4.3 Case Study: Formalization

Let us first estimate $d(I, \tilde{I}) = \int |\Delta I(x)|^p dx$. To find the upper bound D for this distance, we need to estimate the difference $\Delta I(x) = \tilde{I}(x) - I(x)$ between the reconstructed and the original images, and we also need to estimate the area over which we integrate this difference.

Let Δ_0 denote a “typical” error of reconstructing an image from its lossy compression. Then, we can expect that on average, $|\Delta I(x)| \leq \Delta_0$ and $|\Delta I(x)|^p \leq \Delta_0^p$.

Let us now estimate the area. In the above-described problems, we are only interested in the points x which are reasonably bright, i.e., for which the brightness $I(x)$ exceeds a certain threshold I_0 . In such problems, after we reconstruct the image, we can eliminate all the values for which $\tilde{I}(x) < I_0$. Thus, when the reconstruction is good enough, both the original image $I(x)$ and the reconstructed image $\tilde{I}(x)$ are concentrated approximately at the same zone. So, their difference $\Delta I(x)$ is also concentrated on this same zone.

Let L denote the linear size of the entire image $[0, L] \times [0, L]$ (including pixels with 0 intensity). Let r denote the portion of the image which we expect to be informative (i.e., filled with non-zeros). Then, the total area of the informative part of the image is approximately equal to $r \cdot L^2$.

Since $|\Delta I(x)|^p \leq \Delta_0^p$, and the integration area is

equal to $r \cdot L^2$, we have

$$d(I, \tilde{I}) = \int |\Delta I(x)|^p dx \leq \int \Delta_0^p dx = \Delta_0^p \cdot r \cdot L^2.$$

Thus, we can take $D = \Delta_0^p \cdot r \cdot L^2$.

For each component c_i of the center of gravity, e.g., for the 1st component, we have

$$c_1(I) = \frac{\int x_1 \cdot I(x) dx}{\int I(x) dx}.$$

In our problems, the value d of the denominator stays approximately the same, namely,

$$d \approx I_{av} \cdot r \cdot L^2.$$

Therefore, when we substitute $\tilde{I} = I - \Delta I$ into the above formula and ignore quadratic and other terms, we conclude that $a(x) = x_1/d$. Therefore,

$$A = \int |a(x)|^q dx = \frac{1}{d^q} \cdot \int_0^L dx_2 \int_0^L |x_1|^q dx_1 = \frac{1}{d^q} \cdot L \cdot \frac{L^{q+1}}{q+1}.$$

We want to find the value p which minimizes the product

$$D^{1/p} \cdot A^{1/q} = \Delta_0 \cdot r^{1/p} \cdot L^{2/p} \cdot \frac{1}{d} \cdot L^{1/q} \cdot L^{1+1/q} \cdot (q+1)^{-1/q}.$$

4.4 Case Study: Optimization

Some factors in the minimized expression, such as Δ_0 , do not depend on p at all. So, when we find the minimum of the product, we can as well divide by these factors and only minimize what remains without changing the value of p for which this product takes the smallest possible value. Since $1/p + 1/q = 1$, the product of all powers of L in this expression is equal to $L^{2/p+2/q+1} = L^3$, so these terms can also be eliminated without changing the desired value of p . As a result, we must find p as a solution to the following problem: $r^{1/p} \cdot (q+1)^{-1/q} \rightarrow \min$. Since $1/q = 1 - 1/p = (p-1)/p$, we have $q = p/(p-1)$ and $q+1 = (2p-1)/(p-1)$, so the minimization problem takes the form:

$$r^{1/p} \cdot (2p-1)^{1/p-1} \cdot (p-1)^{1-1/p} \rightarrow \min.$$

Minimizing this expression is equivalent to minimizing its logarithm

$$\frac{1}{p} \cdot \ln(r) - \left(1 - \frac{1}{p}\right) \cdot \ln\left(\frac{2p-1}{p-1}\right) \rightarrow \min.$$

Differentiating the minimized function relative to p and equating the derivative to 0, we get the following equation:

$$-\frac{1}{p^2} \cdot \ln(r) - \frac{1}{p^2} \cdot \ln\left(\frac{2p-1}{p-1}\right) - \left(1 - \frac{1}{p}\right) \cdot \left(\frac{2}{2p-1} - \frac{1}{p-1}\right) = 0.$$

If we subtract the fractions, multiply both sides by p^2 , and move $\ln(r)$ to the other side, then we get the following equation

$$\ln(r) = -\ln\left(\frac{2p-1}{p-1}\right) + \frac{p}{2p-1}, \quad (1)$$

or, equivalently, $r = \frac{p-1}{2p-1} \cdot e^{p/(2p-1)}$. In particular, the L^2 -method ($p = 2$) is optimal for $r = e^{2/3}/3 \approx 0.65$.

If we differentiate the right-hand side of the equation (1) and add the resulting fractions, we conclude that this derivative is equal to $\frac{p}{(p-1) \cdot (2p-1)}$, i.e., it is always positive. Thus, $\ln(r)$ is an increasing function of p and hence, p is a increasing function of $\ln(r)$ and hence, of r .

When $p \rightarrow 1$, we get $\ln(r) \rightarrow -\infty$ and $r \rightarrow 0$. When $p \rightarrow \infty$, we get $\ln(r) \rightarrow -\ln(2) + 0.5$, i.e., $r \rightarrow \sqrt{e}/2 \approx 0.82$. Thus, we arrive at the following conclusions.

5 Image Compression: Conclusions

In many image-processing situations, we must select the optimal lossy compression scheme. Due to the lossiness of such compression schemes, the reconstructed image \tilde{I} may differ from the original image I , i.e., $\Delta I(x) = \tilde{I}(x) - I(x) \neq 0$. We show that a natural way to select an optimal compression scheme is to select a scheme for which the average value of the quality metric $d(I, \tilde{I}) = \int |\Delta I(x)|^p dx$ if the smallest possible. The value p should be selected depending on what images we expect:

- If we expect a small image (e.g., a microcalcification in mammography), then the optimal value of p is close to 1, corresponding to $d(I, \tilde{I}) = \int |\Delta I(x)| dx$.
- When r increases, the value of p increases, and it reaches $p = \infty$, which corresponds to $d(I, \tilde{I}) = \max |\Delta I(x)|$, for $r = \sqrt{e}/2 \approx 0.82$.

In general, to find the optimal value of p , the must solve the equation (1).

6 Future Work: From Image Compression to Control Compression

From the mathematical viewpoint, an image can be viewed as a function $I(x_1, x_2)$ of two coordinates x_1 and x_2 . Therefore, compression techniques for images can be also used to compress other functions of several variables. Another important use of such functions in microsystems is in control, where the control function $C(x_1, x_2)$ describes the value of control to be used for given inputs x_1 and x_2 .

One of the authors (YY) has developed such compression technique for *fuzzy controllers* [13]. To explain these techniques, let us consider a system with inputs x_1, x_2 and control rules

$$\text{“if } A_{1,i}(x_1) \text{ and } A_{2,j}(x_2) \text{ then } u = u_{i,j}\text{”},$$

where $A_{\ell,j}$ are fuzzy properties, and $u_{i,j}$ are given values. Our goal is to “compress” the corresponding control function, i.e., to reduce the number of corresponding control rules.

We assume that for $\ell = 1, 2$, the corresponding properties $A_{\ell,i}$ form a *fuzzy partition*, i.e., for every x_ℓ , $\sum_i A_{\ell,i}(x_\ell) = 1$. If we use $a \cdot b$ as a t-norm, addition for combining rules, and center-of-gravity defuzzification, the resulting control is

$$u(x_1, x_2) = \sum_{i,j} u_{i,j} \cdot A_{1,i}(x_1) \cdot A_{2,j}(x_2). \quad (2)$$

The fewer non-zero coefficients $u_{i,j}$, the fewer rules we need. So, to decrease the number of rules, we represent the corresponding bilinear form

$$F = \sum_{i,j} u_{i,j} \cdot y_i \cdot z_j$$

as

$$F = \sum_{p=1}^P u'_p \cdot Y_p \cdot Z_p,$$

where Y_p are linear combinations of y_i , Z_p are linear combinations of z_j , i.e.,

$$Y_p = \sum_i c_{p,i}^{(1)} \cdot y_i,$$

$$Z_p = \sum_j c_{p,j}^{(2)} \cdot z_j,$$

and the number P is the smallest possible. Then, we can describe the fuzzy controller as

$$u(x_1, x_2) = \sum_{p=1}^P u'_p \cdot A'_{1,p}(x_1) \cdot A'_{2,p}(x_2), \quad (3)$$

where

$$A'_{\ell,p}(x_\ell) = \sum_i c_{p,i}^{(\ell)} \cdot A_{\ell,i}(x_\ell)$$

are the corresponding linear combinations. Thus, P rules are sufficient.

If the matrix $u_{i,j}$ is symmetric, then the desired representation of the bilinear form corresponds to eigenvalues u'_p and eigenvectors $Y_p = Z_p$; in general, the desired representation is known as a Singular Value Decomposition (SVD). The value P corresponds to the maximum number of nonzero singular values.

A similar reduction can be achieved if we have three or more inputs x_i . Practical examples (see, e.g., [13]) show that this reduction can indeed be drastic.

If, instead of the above *lossless* compression, we allow *lossy* compression and ignore the rules whose contributions are small, we can get an even smaller number of rules. This can be done by dropping the rules that have relatively small nonzero singular values. It has been shown that the resultant error between the original fuzzy controller and the reduced one is bounded by the sum of the discarded singular values (see [13]).

On the other hand, we may also apply the compression technique for fuzzy controller to image compression. The original image function, $I(x_1, x_2)$, can actually be viewed as a fuzzy controller of the form (2). After reduction by SVD methods, $I(x_1, x_2)$ is approximated by the form (3), with $A'_{1,p}(x_1)$ and $A'_{2,p}(x_2)$ being piecewise linear functions of x_1 and x_2 , respectively. Hence, in the main idea of Section 4, we can use as degraded image \tilde{I} the expression of (3) and as ΔI the maximum error bound, which is the sum of discarded singular values. Ensuing analysis can thus be simplified as relevant integration are more readily executed. The goal here is then to find the maximum number of singular values to discard which would still generate acceptable performance.

Acknowledgments

This work was supported in part by NASA under cooperative agreement NCC5-209, by NSF grants No. DUE-9750858 and CDA-9522207, by the United Space Alliance, grant No. NAS 9-20000 (PWO C0C67713A6), by the Future Aerospace Science and Technology Program (FAST) Center for Structural Integrity of Aerospace Systems, effort sponsored by the Air Force Office of Scientific Research, Air Force Materiel Command, USAF, under grant number F49620-95-1-0518, and by the National Security Agency under Grants No. MDA904-98-1-0561.

References

- [1] R. E. Edwards, *Functional analysis: theory and applications*, Dover, N.Y., 1995.
- [2] P.C. Fishburn, *Utility Theory for Decision Making*, John Wiley & Sons Inc., New York, 1969.
- [3] P.C. Fishburn, *Nonlinear preference and utility theory*, The John Hopkins Press, Baltimore, MD, 1988.
- [4] O. Kosheleva, "Symmetry-group justification of maximum entropy method and generalized maximum entropy methods in image processing", In: G. J. Erickson, J. T. Rychert, and C. R. Smith (eds.), *Maximum Entropy and Bayesian Methods*, Kluwer, Dordrecht, 1998, pp. 101–113.
- [5] O. Kosheleva et al., "Compression degradation metrics for analysis of consistency in microcalcification detection", *Proc. 1998 IEEE Symposium on Image Analysis and Interpretation*, April 5–7, Tucson, Arizona, USA, pp. 35–40.
- [6] O. Kosheleva et al., "Operations with Fuzzy Numbers Explain Heuristic Methods in Image Processing", *Proceedings of the International Conference on Information Processing and Management of Uncertainty in Knowledge-Based Systems (IPMU'98)*, Paris, France, July 6–10, 1998, pp. 265–272.
- [7] O. Kosheleva, C. Mendoza, and S. D. Cabrera, "Task-specific image quality metrics for lossy compression", In: I. Kadar (ed.), *Signal Processing, Sensor Fusion, and Target Recognition VIII*, Proceedings of the SPIE/International Society for Optical Engineering, Vol. 3720, Orlando, FL, 1999, pp. 397–408.
- [8] O. M. Kosheleva et al., "Metrics for evaluation and control of lossy compression effects on the processing of SMD images", *Proceedings of the 1999 IEEE Midwest Symposium on Circuits and Systems*, Las Cruces, New Mexico, August 8–11, 1999, pp. 1147–1150.
- [9] D. R. Luce and H. Raiffa, *Games and Decisions, Introduction and critical survey*, John Wiley & Sons, Inc., New York, 1957.
- [10] R. B. Myerson, *Game theory. Analysis of conflict*, Harvard University Press, Cambridge, MA, 1991.

- [11] H. T. Nguyen and V. Kreinovich, *Applications of continuous mathematics to computer science*, Kluwer, Dordrecht, 1997.
- [12] P. Suppes, D. M. Krantz, R. D. Luce, and A. Tversky, *Foundations of measurement. Vol. II. Geometrical, threshold, and probabilistic representations*, Academic Press, San Diego, CA, 1989.
- [13] Y. Yam, “Fuzzy approximation via grid point sampling and Singular Value Decomposition,” *IEEE Transactions on Systems, Man, and Cybernetics*, 1997, Vol. 27, No. 6, pp. 933–951.

the same value somewhere ($\Delta I_1(x) = \Delta I_2(y)$), the corresponding values of c are the same. Hence, c can only depend on λ :

$$U'(\lambda \cdot \Delta I(x)) = c(\lambda) \cdot U'(\Delta I(x)).$$

This is a known functional equation, whose only differentiable solutions are $F'(z) = c_1 \cdot z^\alpha$ for some real numbers c_1 and α (see, e.g., [11]). Since the function $U(z)$ is everywhere differentiable, the value $U'(0)$ must be finite, i.e., $\alpha \geq 0$. Hence, $U(z) = c_2 \cdot z^p + c_2$, where $p = \alpha + 1 \geq 1$. From $U(0) = 0$, we can conclude that $c_2 = 0$. The theorem is proven.

Appendix: Proof of the Theorem

This proof is similar to the proofs from [4]; for a general description of how symmetry requirements can help, see [11].

From unit-invariance, one can conclude that if the change $\Delta I(x) \rightarrow \Delta I(x) + \varepsilon \cdot \delta I(x)$ does not affect $B(\Delta I)$, then this change should not affect $B(\lambda \cdot \Delta I)$ either. Since $U(z)$ is a differentiable function, when $\varepsilon \rightarrow 0$, the change in $B(\Delta I) = \int U(\Delta I(x)) dx$ is asymptotically equal to

$$\varepsilon \cdot \int U'(\Delta I(x)) \cdot \delta I(x) dx,$$

where $U'(z)$ is the derivative of $U(z)$, and the corresponding change in $B(\lambda \cdot \Delta I)$ is asymptotically equal to

$$\varepsilon \cdot \lambda \cdot \int U'(\lambda \cdot \Delta I(x)) \cdot \delta I(x) dx.$$

Thus, if $\int U'(\Delta I(x)) \cdot \delta I(x) dx = 0$, then we have

$$\int U'(\lambda \cdot \Delta I(x)) \cdot \delta I(x) dx = 0.$$

In terms of L^2 -metric $\int (f(x) - g(x))^2 dx$ on the space of all functions, the condition of this implication means that the function δI is orthogonal to the function $U'(\Delta I)$. Thus, the implication says that every function δI which is orthogonal to $U'(\Delta I)$ is also orthogonal to $U'(\lambda \cdot I)$. From the geometric viewpoint, this can happen only if the functions $U'(\Delta I)$ and $U'(\lambda \cdot I)$ are collinear, i.e., when $U'(\lambda \cdot \Delta I(x)) = c \cdot U'(\Delta I(x))$ for all x .

The coefficient c does not depend on x , but it may depend on λ and also on the function $x \rightarrow \Delta I(x)$. From the above condition, however, we can conclude that the coefficient c depends only on the value $\Delta I(x)$ at a given point x . So, if two different functions have